

Interior Wall Coat 40

1. PRODUCT DESCRIPTION

Ceratech's Interior Wall Coat 40 is an emulsion of high grade acrylic resins in water. It dries by evaporation to yield a tough, velvety, non-yellowing, water repellent surface with exceptional abrasion resistance. Interior Coat 40 will also accept all universal tints that will not fade with age.

Unlike other coatings, it contains the added advantage of ceramic particles. These particles are the heat and cold dissipating elements in Ceratech's Interior Wall Coat 40 that give it the ability to save on heating and cooling costs. Ask your local distributor for more information.

2. OUTSTANDING FEATURES

Non-toxic	Stain Resistant
Water Borne	Flexible
Energy Savings	Five (5) year Warranty
Color Fast	Labor, Time, & Cost Saving
Non-yellowing	Clean up with soap & water
Mildew Resistant	Non Chaulking

3. APPLICATION

Surfaces should be clean, dry and sound. Existing surface dirt, oil, tar, grease and film should be removed from surface by approved methods prior to application.

Ceratech's Interior Wall Coat 40 can be applied to other surfaces. Examples are: wood, stucco, wallboard, masonry, and primed metal.

Ceratech Interior Wall Coat 40 can be applied by brush, roller or airless spray equipment. It should be applied evenly without buildup. Multiple coats are recommended. See Application Specifications in the distributor manual for your particular application.

4. CAUTIONS AND WARNINGS

Do not take internally. Avoid contact with eyes. If solution does come in contact with eyes, flush immediately with water and contact physician for medical attention. Avoid prolonged contact with skin or breathing of spray mist. **KEEP OUT OF THE REACH OF CHILDREN. KEEP FROM FREEZING.**

5. TYPICAL PERFORMANCE PROPERTIES

Total Emittance

94%		ASTM E 408-71
-----	--	---------------

Spectral Reflectance

83.6%		ASTM E 903
-------	--	------------

Fungal Resistance

No fungal growth on sample		Tropical chamber ASTM D-3273-73T
----------------------------	--	-------------------------------------

Chalking

10		ASTM D4214
----	--	------------

Checking

10		ASTM D660
----	--	-----------

Cracking

10		ASTM D661
----	--	-----------

Blistering

10		ASTM D714
----	--	-----------

Flaking

10		ASTM D772
----	--	-----------

COVERAGE CHART

Surface	Approx. Cov. (Sq.Ft.Per Gal)
Wallboard	200 to 300
Stucco	150 to 200
Masonry	200 to 300
Wood	200 to 300
Primed Metal	200 to 300

Coverages are based on 1 gallon units and single coat applications. Coverages are approximate for normal substrates. Under irregular conditions more product is required.