

# Rubber Coat 20

## 1. PRODUCT DESCRIPTION

Ceratech's Elastomeric Rubber Coat 20 is a water-borne dispersion of aliphatic urethanes incorporated with high quality solids. Ceratech's Rubber Coat 20 has especially good adhesion to a wide variety of substrates and provides resistance to abrasion and ultraviolet light. Rubber Coat 20 is primarily used on single-ply roofs. Due to single-ply roofs inability to withstand harsh ultraviolet light, Rubber Coat 20 has become a very beneficial and cost effective method of stopping further degradation. Ask your local distributor for more information.

## 2. OUTSTANDING FEATURES

Non-toxic	Superior Adhesion to Single-Ply
Water Borne	Roofing, Metals, and Plastics
Energy Savings	Abrasion Resistant
Chemical Resistance	Ten (10) year Warranty
Cost Efficiency	Clean up with soap & water

## 3. APPLICATION

Surface should be clean, dry and sound. Existing surface dirt, oil, tar, grease, and film should be removed from surface by approved methods prior to application.

Rubber Coat 20 can be applied by brush, roller, or airless sprayer. Rubber Coat 20 is used as a primer coat for single-ply roofing material. Rubber Coat 20 should be top coated with Pond Coat 30 for an insulative effect. See Application Specifications in the distributor manual for your particular application.

## 4. CAUTIONS AND WARNINGS

Do not take internally. Avoid contact with eyes. If solution does come in contact with eyes, flush immediately with water and contact physician for medical attention. Avoid prolonged contact with skin or breathing of spray mist. **KEEP OUT OF THE REACH OF CHILDREN. KEEP FROM FREEZING.**

## 5. TYPICAL PERFORMANCE PROPERTIES

81.5%	<b>Solar Reflectance</b> ASTM E-903-88
No Effect	<b>Rusting</b> ASTM D610
No effect	<b>Blistering</b> ASTM D714

### COVERAGE CHART

Surface	Approx. Cov. (Sq.Ft.Per Gal)
Single-Ply Roofing	100
Membrane Roofing	100

Coverages are based on 1 gallon units and single coat applications. Coverages are approximate for normal substrates. Under irregular conditions more product is required.